Atlas Copco Portable Air Compressors



XAMS 407 XATS 377 XAHS 347 XAVS 307

The next big thing is small.

Atlas Copco is a leading manufacturer of portable compressed air machines in the world, and through constant search of innovation can superior products be developed. The combination of performance, reliability, economy and convenience has resulted in an innovative range of single axle high capacity air compressors used in a variety of industries.





The next big thing is small.

Our constant search for innovation and our commitment to your needs has resulted in a superior product providing the utmost in performance, reliability, economy and versatility.

As sandblasting and drilling have become principal cornerstones of their work, priority was not only given to performance and reliability, but also to improvement of mobility and manoeuvrability. Smaller and lighter means the operator can move to the next work point easier and faster, without the need for supplemental moving equipment.

Total cost of ownership through lower fuel consumption can be realized with the help of Fuel $Xpert^{TM}$.

Above all, Atlas Copco compressors are built for reliability and easily maintained, providing many years of trouble free performance.

Technical data

Туре		XAMS 407	XATS 377	XAHS 347	XAVS 307
Normal effective working pressure	bar(e)	8.6	10.3	12	14
	psig	125	150	175	204
Actual free air delivery	1/sec	400	365	339	310
according to ISO 1217 ed.3 1996 annex D	m³/min	24.0	21.9	20.4	18.6
	cfm	848	774	719	657
Max. Sound power level (LWA)*	dB(A)	100	100	100	100
Max. Sound pressure level at 7m	dB(A)	76	76	76	76
Oil Capacity	1	31	31	31	31
Max. ambient temperature	°C	50	50	50	50

Engine Caterpillar

Туре		Caterpillar C 7 acert T3			
Number of cylinders		6	6	6	6
Output at rated speed	kW	186	186	186	186
Swept volume	1	7.2	7.2	7.2	7.2
Engine speed (nominal)	rpm	2000	2000	2000	2000
Engine speed (unloaded)	rpm	1300	1300	1300	1300
Capacity oil system	1	22	22	22	22
Capacity cooling system	1	47	47	47	47
Capacity of fuel tank**	1	290	290	290	290

Unit dimensions (overall)		Fixed towbar	Adjustable towbar
Length	m	5.074	5.070 / 5.508
Width	m	1.988	1.988
Height	m	2.092	2.094

Weight (ready-to-operate)

with undercarriage	kg	3400	
	lb	4780	

^{*}complies with 2000/14/EC, 84/533/ECC AND 85/406/EEC limits



Features

- Small dimensions, light weight
- Single axle mounted
- Low noise output
- FuelXpert[™] for optimized fuel consumption
- Full shift fuel tank
- Single side service points
- Full length service doors
- Centralized fluid drains
- Electronic multi-function controller

Advantages

- Low total cost of ownership
- Easy to transport
- Easy to manoeuver at worksite
- Ideal for urban use
- Operator & environmental safe
- Comprehensive monitoring
- Best fuel economy in class



^{**}option: expandable with extra fuel tank of 100l